SUWANNEE COUNTY SCHOOL BOARD INVITATION TO BID #17-212 "New Mobile Kitchen/Food Trailer"

Scope of Work: Suwannee County School Board is seeking bids from dealers or individuals for the purchase of a new Mobile Kitchen/Food Trailer. The services to be provided under this bid include, but are not limited to meeting the minimum criteria as requested below:

- 1. 8'6" wide x 20' long Trailer Manufacturing Mobile Kitchen Trailer
- 2. Custom reinforced walk on roof
- 3. Two pairs of heavy duty scissor type stabilizer jacks located on front & rear of trailer, 5000 lb static load capacity each
- 4. Extended three piece 'A' frame (5' long tongue) with a heavy duty tongue jack & sand pad
- 5. 2 5/16" top mount coupler with replaceable locking dog assembly
- 6. D.O.T. compliant 5/16" safety chains with Clevis safety slip hook & latch
- 7. 6"x2" rectangular steel tube main rails with equal height 'C' section cross members with square outriggers & steel side plates steel cross members on 16" center
- 8. Two 6000 LB (12,000 GVWR) 10 degree up torsion axles with 12" x 2" electric brakes, E/Z lube & 8 on 6.5 hubs and drums with weather resistant wiring package
- 9. Four ST235/80R16 load range 'E' radial tires mounted on an 8 bolt electro deposition coated silver bullet hole wheel
- 10. Chassis fully under coated with CPC (Corrosion Preventative Compound)
- 11. 7' interior height
- 12. Custom curbside 3 section TEMPERED GLASS SERVING WINDOW (45" high x 69" wide), with 1 display/picture window & 2 vertical slider windows with screens (16" mesh) that will serve customers lift up awning (approx. 113" wide) with 2 keyed flush locks for security & gas assist awning rods to raise & secure awning in upright position
- 13. 36" wide lockable pre-framed rear entry door with screen (16" mesh), flush lock & integrated dead bolt Note: door opening should be as close to C/S counter as possible
- 14. ¾" exterior grade plywood floor
- 15. Non-porous and easily cleanable one piece heavy duty commercial grade RTP (Rubber Tread Plate) flooring over exterior grade plywood floor
- 16. Smooth and easily cleanable non-porous white aluminum ceiling liner with no exposed utility lines, piping, conduit or wiring bonded for a smooth look
- 17. Smooth and easily cleanable non-porous white aluminum interior sidewall liner with no exposed utility lines, piping, conduit or wiring bonded for a smooth look
- 18. Fully insulated sidewalls and ceiling
- 19. 84" long white laminated interior overhead cabinet with latching cabinet doors along curbside wall above the sink assembly
- 20. 12" deep x 122" long white aluminum interior overhead storage tray/shelf along curbside wall
- 21. 12" deep x 138" long white aluminum interior overhead storage tray/shelf along roadside wall
- 22. 24" deep x 122" long x 30" high interior counter along curbside wall Note: cover top with stainless steel
- 23. Custom 18" deep x 122" long x approx 12" high interior underneath shelf below C/S

- counter along curbside wall Note: cover top with stainless steel
- 24. Custom 10" deep x 69" long stainless steel exterior fold down condiment counter in front of curbside serving window
- 25. 100 amp, 120/240v service panel/box with a 100 amp main breaker, approximately 20' long shoreline power cord for electrical connection and through floor cable hatch to run power cord outside CRITICAL: balance panel/legs accordingly --- Note: mount panel along rear wall toward R/S above work top table
- 26. Twelve 20 amp, 120v GFI duplex wall receptacles Note: use cord drops where applicable
- 27. Three 4' double fluorescent light fixtures with diffuser covers include on/off light switch)
- 28. Three single exterior weatherproof halogen floodlights on a GFI breaker include interior on/off wall switch
- 29. Custom 24" deep x 84" long x 36" high white laminated enclosure/cabinet with latching cabinet doors for commercial NSF APPROVED stainless steel 3 compartment "Deli" sink with single faucet & integrated drain boards on each side (bowl size approx. 10x14x10) include separate stainless steel hand sink & faucet with divider/splash guard to separate the hand sink from the 3 compartment sink all sinks should have hot & cold running water under pressure NOTE: cover top with stainless steel
- 30. Removable cutting board (NSF or equal) to place over the 3 compartment sink
- 31. On demand water pump with on/off wall switch
- 32. 40 gallon fresh water tank (NSF or equal) located under the sink assembly concealed in custom cabinet enclosure for a clean and professional look 1/2" hot and cold NSF Pex water lines
- 33. 6 gallon, 120v hot water heater located under the sink cabinet/enclosure
- 34. Exterior water hook up with back flow preventer include keyed locking door
- 35. 50 gallon waste water holding tank located under the trailer lower and away from the fresh water tank per regulatory requirements include waste vent stack, 1 1/2" PVC drain lines & back flow preventer per code (Note: waste tank should be 15% larger & or greater than water tank)
- 36. A dump valve located under the trailer for easy waste removal
- 37. .030 pre-finished "WHITE" exterior aluminum "BONDED"
- 38. Aluminum teardrop fenderettes over wheel wells
- 39. 120v, 15,000 BTU roof mounted air conditioner with a 5600 BTU heat strip
- 40. 14"x14" screened (16" mesh) translucent roof vent with crank include a roof vent cover for rain protection while vent is open
- 41. S.A.E. color coded 12v electrical system, D.O.T. required exterior lighting package
- 42. D.O.T. 'A' frame (tongue) mounted battery with breakaway switch
- 43. 7 way round trailer end connector (7 way RV blade style)
- 44. Custom anodized front and rear corner covers
- 45. Four chrome ABS hub covers and trim rings
- 46. Honda 10KW gasoline standby generator include

In addition to the trailer, the following equipment must be included

- NSF APPROVED 19 cu. ft. standard commercial stainless steel stand up refrigerator (SW) – Note: Left Hand Hinge
- 2. NSF APPROVED 36" commercial stainless steel refrigerated sandwich prep unit with top

- pans, lid and cutting board (BA)
- 3. NSF APPROVED 9 cu. ft. commercial counter top glass door display refrigerator manufactured by True, model GDM-9-LD
- 4. Two NSF APPROVED commercial insulated hot holding cabinet/proofers with clear Lexan door
- 5. NSF APPROVED 60" long x 30" deep commercial stainless steel work top table with an adjustable underneath shelf
- 6. NSF APPROVED 72" long x 30" deep commercial stainless steel work top table with an adjustable underneath shelf
- 7. Paper towel holder and soap dispenser next to the hand sink
- 8. ABC fire extinguisher

Please include pictures of similar Mobile Kitchen/Food Trailers that your company has completed for other school districts or businesses.